Technical Data Sheet
RED IRON OXIDE 130S

Description: Inorganic pigment, red iron oxide powder, red-yellowish undertone.

Type: 130S, Pigment Red 130

Characteristics:

- Highly stable to sunlight
- Easy dispersion
- Can be used in construction materials such as mortars, cement flooring, and concrete, as well as for paints, rubber, and plastic.

CAS No.: 1309-37-1/215-168-2

Specifications

Content ($Fe_2O_3 \cdot \alpha H_2O$)	%	≥97	ISO1248
Extender pigment	%	≤ 3	ISO 1248
Oil absorption	ml/100 g	15 – 25	ISO 787-5
Residue on 325 mesh	%	≤ 0.3	ISO 787-7
Water-soluble salts	%	≤ 0.3	ISO 787-3
Moisture	%	≤ 1.0	ISO 787-2
pH value		3 – 7	ISO 787-9
Loss on ignition (1,000°C, ½ h)	%	≤ 1.0	DIN 55913
Bulk density	g/cm^3	0.7 – 1.1	ISO 787-11

This technical data sheet for Red Iron Oxide 130S is the property of TLA

Technical Data Sheet
RED IRON OXIDE 130S

Specific gravity	g/cm^3	5.0	ISO 787-10
Particle size (BET)	µm	0.17	Electron micrographs
Dispersibility (Hegman)	µm	20 / 25 / 30	ISO 787-20
Tinting strength	%	95 – 105	ISO787-24
Color difference (Delta E)		≤ 1.0	ISO787-1

Packaging

- 25kg paper bags
- 1,000 kg big bags, palletized

Transport and Storage

Protectfromweatherexposure. Store in a dry place.

Safety

Theproduct is not classified as hazardous under EC 1907/2006 and EC 1272/2008.

This technical data sheet for Red Iron Oxide 130S is the property of TLA